

VS1063 APPNOTE: PLAYBACK AND RECORDING

Microcontroller example code

All information in this document is provided as-is without warranty. Features are subject to change without notice.

Revision History			
Rev.	Date	Author	Description
1.10	2016-05-09	HH	Changed quick sanity check registers.
1.02	2012-11-28	HH	Untabified player1063.c.
1.01	2012-11-27	HH	Bug fixes to the code.
1.00	2012-11-23	HH	Initial version.

Contents

VS1063 AppNote: Playback and Recording Front Page	1
Table of Contents	2
1 Playback and Recording on VS1063	3
1.1 vs10xx_uc.h	3
1.2 vs1063a-patches.plg	3
1.3 player.h	4
1.4 player1063.c	5
1.5 Main Program	5
2 Latest Version Changes	6
3 Contact Information	7

List of Figures

1 Playback and Recording on VS1063

The VS1063 Datasheet tells how to play back and record files using VS1063 as a slave processor. This AppNote and software package provides the same information as generic microcontroller C code.

Note that this code is not written for any particular microcontroller. It has been written in standard C, and the few parts having to do with SPI bus communication that are environment-specific, have not been included.

To create your own program, read the included source code, make the modifications and additions suggested in this document, compile with your favourite microcontroller compiler, and run.

The rest of this Chapter introduces the files in this package.

1.1 vs10xx_uc.h

Contains symbols for VS10xx registers and register bits.

1.2 vs1063a-patches.plg

This file is not included in this package.

Get this file from the latest *VS1063 Patches* package, available at <http://www.vlsi.fi/en/support/software/vs10xxpatches.html>

For best playback and recording quality, keep this file updated with the latest version.

1.3 player.h

Definitions and prototypes for the player. The following functions are declared:

int VSTestInitHardware(void)

Initializes microcontroller for VS10xx operations. You need to add the microcontroller-specific code to this file in `player1063.c`.

Returns 0 on success, non-zero on failure.

int VSTestInitSoftware(void)

Makes a software reset for VS1063 and initializes it for use, including loading the patches package.

Returns 0 on success, non-zero on failure.

int VSTestHandleFile(const char *fileName, int record)

Plays back a given file or records to it, depending on whether `record` is 0 or 1.

u_int16 ReadSci(u_int8 addr)
void WriteSci(u_int8 addr, u_int16 data),
int WriteSdi(const u_int8 *data, u_int8 bytes)

You need to provide these functions that read and write from the VS1063's Serial Control and Data SPI Interfaces. For details on how to implement these functions, see Application Note *Connecting VS10xx SPI Buses*, available at <http://www.vlsi.fi/en/support/applicationnotes.html>

void SaveUIState(void)
void RestoreUIState(void)
int GetUICommand(void)

You need to provide these functions if you want your player to have a simple demonstration user interface.

`SaveUIState()` saves the user interface environment before execution, and `RestoreUIState()` restores it. In many cases these may be implemented as empty functions.

`GetUICommand()` should return -1 if there are no messages and -2 if forceful cancel is requested. By returning 63 (ASCII code for '?'), you get the list of other options from the player or recorder. See `player1063.c` for details.

1.4 player1063.c

Contains the implementation for VS1063 playback and recording.

See the source code for details.

1.5 Main Program

Your main program, which is not included in this package, should look something like this:

```
int main(...) {
    if (VSTestInitHardware() || VSTestInitSoftware()) {
        printf("Failed initializing VS10xx, exiting\n");
        exit(EXIT_FAILURE);
    }

    /* ... */

    /* Playback example. You can call these functions many times in a row
       because they leave VS1063 in a known state. */
    VSTestHandleFile("MyPlayFile.mp3", 0);

    /* Recording example */
    VSTestHandleFile("MyRecordFile.mp3", 1);

    /* ... */
}
```

2 Latest Version Changes

Version 1.10, 2016-05-09

The following source code changes have been made:

- Changed quick sanity check registers in this package from registers SCI_HDAT0 and SCI_HDAT1 to SCI_AICTRL1 and SCI_AICTRL2.
- Added chip type recognition to this package. Now code will refuse to run if the chip is not a VS1063.

Version 1.02, 2012-11-28

Untabified *player1063.c*.

Version 1.01, 2012-11-27

Bug fixes to the example code files in this package.

Version 1.00, 2012-11-23

Initial version.

3 Contact Information

VLSI Solution Oy
Entrance G, 2nd floor
Hermiankatu 8
FI-33720 Tampere
FINLAND

URL: <http://www.vlsi.fi/>
Phone: +358-50-462-3200
Commercial e-mail: sales@vlsi.fi

For technical support or suggestions regarding this document, please participate at
<http://www.vsdsp-forum.com/>
For confidential technical discussions, contact
support@vlsi.fi