



PRODUCT SPECIFICATIONS @				
TAPE WIDTH	ØA (MAX)	ØN (MIN)	W1 ±2.0 (MAX)	W2 (MAX)
12MM	330	100	12.4	18.4
16MM	330	100	16.4	22.4
24MM	330	100	24.4	30.4
32MM	330	100	32.4	38.4
44MM	330	100	44.4	50.4
56MM	330	100	56.4	62.4

SURFACE RESISTIVITY			
LEGEND	SR RANGE	TYPE	COLOUR
A	BELOW 10 ¹²	ANTISTATIC	ALL TYPES
B	10 ⁶ TO 10 ¹¹	STATIC DISSIPATIVE	BLACK ONLY
C	10 ⁵ AND BELOW 10 ⁵	CONDUCTIVE (GENERIC)	BLACK ONLY
C	10 ⁵ TO 10 ⁹	CONDUCTIVE (CUSTOM)	BLACK ONLY

NOTE "L"

ANTISTATIC (ALL COLORS)
 STATIC DISSIPATIVE (BLACK)
 CONDUCTIVE (BLACK)

- NOTE:
1. ALL LOGO MUST COME WITH A BLIND INSERT.
 2. ALL SURFACE SANDBLAST UNLESS OTHERWISE STATED.
 3. FOR PRODUCT DRAWING ONLY.
 4. CONDUCTIVE SR BASED ON CUSTOMER REQUEST.

TITLE : 13X4 E Z REEL (3 WINDOWS)			
S.R : REFER TO TABLE	TOOL NO :	CPAK 2087 PDI :	PDI/XXX/99
SCALE : NTS	SHRINKAGE :	0.45%	TOLERANCE :
REV. : REFER TO DWG REF.	MATERIAL :	PS	X.X ±0.25
UNIT : MM	WARPAGE :	--	X.XX ±0.13
SHT : 1/1	NAME :	DATE :	ANGLE :
	DRAWN/AFIZAH	180505	X ±1°
	CHECK/SHUKRI	180505	X.X ±0.5°

DWG-REF.	REV.
22EZ0011	P